


# HARDWARE

**We stock a wide range of steel door parts, including: handles, locks, hinges, seals, panic hardware, closers & stays, cylinders, paint, thresholds, access control hardware, and plates.**

We have tried to include our most commonly requested parts and to make it quick and easy specify your door.



## > MORTICE LOCKS AND LATCHES



### DEADLOCK ALT 1

DeadLock fitted with external cylinder pull, double cylinder and internal escutcheon. Standard for plant rooms.




### DEADLOCK ALT 2

Deadlock fitted with 19mm bolt through handle, and push plate to opposite side. Double cylinder with escutcheons as standard.



### DEADLOCK ALT 3

Deadlock fitted with double 19mm bolt through handle. Double cylinder with escutcheons as standard.



### LATCH

The standard latch fitting is with a pair of 19mm stainless steel levers, suitable for non-secure doors to provide privacy.



### SASHLOCK

The standard fitting for sashlocks is with pair of 19mm stainless levers and a double cylinder deadbolt. Illustrated is optional thumbscrew on non-secure side.




### TOILET LOCK

As the sash lock but the deadbolt is fitted with a privacy/indicator set instead of a cylinder.




### NIGHTLATCH ALT 1

Suitable for automatic locking entrance doors, used manually or in conjunction with an electric strike. Illustrated optional cylinder pull.




### NIGHTLATCH ALT 2

As Alt 1 but fitted with a pull handle. Doors fitted electric strikes provide key access for authorised persons as a manual override, whilst the internal handle gives escape at all times.



### NIGHTLATCH WITH SNIB

The snib allows the locking latch to be secured within the lockcase giving free access. Doors with night latches are normally fitted with closers.



## > MORTICE MULTI-POINT LOCKING



### 3-POINT SASHLOCK

This lock has a sashlock fitted centrally with top & bottom deadbolts. The cylinder operates all locks from the central point. Either a double or euro cylinder & turn can be fitted. An escape version is also available. Note this lock is only available on custom built doors.



### DEADLOCK ALT 2

Additional locks, usually deadlocks, can be fitted to standard doors to aid security. In the illustration are additional deadlocks & a sashlock, which can be fitted in either the upper or lower quarter, or both. The standard option is two locks, one fitted centrally and one in the lower quarter (it is more difficult to apply leverage to the upper half of a door when attacking it).

Additional locks can be fitted with panic bolts and latches to provide night time security, subject to Fire Regulations.


**Typically locks are Hooply Sashlock or Deadlock with Securefast Escutcheons.**

## > LOCKING: ACCESS CONTROL




### MECHANICAL KEYPAD

As standard this is provided with a latchbolt complete with a pair of stainless steel levers and a deadbolt for security, operated by a double cylinder. Illustrated is optional thumbscrew on non-secure side.




### ELECTRIC STRIKE

As standard the door blade is fitted with a nightlatch complete with an external pull handle and internal half-lever. The lever allows manual egress from the inside (this can be replaced by a push button or a secure access system). A half-cylinder can be fitted to allow fail-safe override. The strike can be activated by the full range of secure access systems, eg. keypad, swipe card, etc. Available in 12 or 24vDC and with Fail Open (power to hold strike) or Fail Closed (power to open).



### ELECTRO-MAGNET LOCK, SURFACE MOUNTED

Available in 12 or 24vDC the magnet can be activated by the range of security access systems, eg. keypad, swipe card, etc. It is fitted to the frame with a bolt through armature plate on the door blade. The magnet is locked when power is applied and automatically Fails Open when it is removed. The lock can be fitted to single or double doors.



### ELECTRO-MAGNET LOCK, CONCEALED MOUNTING

The door is fitted with two mag-locks flush mounted into a special frame section, whilst the armature plates are recessed into the door blade. This arrangement is ideal for high traffic entrance doors to offices and flats, as it provides an esthetically pleasing door offering high security and resistance to attack or abuse. The lock can be fitted to single or double doors (on double doors only active leaf operation is allowed).

# FINISHES

> **STANDARD COLOUR FINISHES**

All doors are supplied with a choice of polyester powder coatings from our Standard PPC Colour Range (see chart opposite)



> **OPTIONAL FINISHES**

We also offer a range of optional finishes to fit your exterior or interior application.



Polyester Powder Coated from Non-Standard Colour Range



PVC Laminate from Standard Range



Stainless Steel Brushed, Polished or Patterned



Unfinished for site finishing

Woodgrain PVC Laminates (Recommended for Internal Doors Only)



NORDIK OAK




ASH



MAHOGANY



MAGIC OAK



TEAK



CHERRY



VIRGIN WHITE



GOLDEN OAK